



GERMAN ADLER GMBH

Kennedyallee 93  
60596 Frankfurt am Main  
Phone: +49 69 697 692 10  
Fax: +49 69 697 962 15  
info@german-adler.com  
www.German-Adler.com

## PRODUCT INFORMATION **GERMAN ADLER GEAR OIL SAE 85W-140**

### ***Hypoid-gear oil for motor vehicles and construction machines***

#### **Description**

GERMAN ADLER GEAR OIL SAE 85W-140 is high-alloyed oil, which especially are designed for the lubrication of high-loaded hypoid gears with wide offset as well as for power take-off gears, intermediate gears and secondary gears in motor vehicles and construction machines, but also for non-synchronised manual gears.

#### **Application**

GERMAN ADLER GEAR OIL SAE 85W-140 is recommended for the usage in motor vehicle gears, which are exposed to extreme pressure- and temperature loadings. This especially applies to rear axles with hypoid gearing. Furthermore and in accordance with the manufacturer's instructions they may be used for combined steering and axle gears and for non-synchronised steering transmissions.

In compliance to EEC regulations the quality of GERMAN ADLER GEAR OIL SAE 85W-140 is equivalent according to the following standards / specifications:

- API GL-5
- MAN 342 M-2 (160.000 km oil change)
- MB 235.0/MB 235.6
- MIL-L-2105 D
- ZF TE-ML 05A, 07A, 08, 12E, 16B-D, 17B, 19B, 21A

#### **Advantages/Benefits**

GERMAN ADLER GEAR OIL SAE 85W-140 is oxidation-resistant and provided with thermo-stable EP-additives which allow assured control of extreme tooth flank pressures and trouble-free transmission of great torques.

- good cold flow properties
- high aging stability
- low foaming tendency
- high shear stability
- assured corrosion protection
- elastomer compatibility

#### **Typical characteristics:**

	<b>Unit</b>	<b>Value</b>	<b>Method</b>
<b>Density at 15°C</b>	kg/m <sup>3</sup>	908	DIN 51 757
<b>Viscosity at 40°C</b>	mm <sup>2</sup> /s	405	DIN 51 562
<b>Viscosity at 100°C</b>	mm <sup>2</sup> /s	27,8	DIN 51 562
<b>Pour point</b>	°C	-18	DIN ISO 3016
<b>Flash point</b>	°C	222	DIN ISO 2592
<b>FZG-test A/16,6/90 damage loading step</b>		>12	DIN 51 354

The above data are true and correct to the best of our knowledge and belief and reflect the current state of knowledge and our development effort. All rights to changes reserved! The characteristic data indicated are subject to the repeatability and reproducibility of the given test methods.