



GERMAN ADLER GMBH
Kennedyallee 93
60596 Frankfurt am Main
Phone: +49 69 697 692 10
Fax: +49 69 697 962 15
info@German-Adler.com
www.German-Adler.com

PRODUCT INFORMATION **GERMAN ADLER ATF 9-8**

Description

GERMAN ADLER ATF 9-8 is a high-performance ATF with reduced viscosity based on the most advanced additives and a special base oil composition made of HC synthetic oils and fully synthetic poly-alpha-olefins (PAO).

Application

GERMAN ADLER ATF 9-8 is specifically developed for use in modern 6-, 8-, 9-speed automatic transmissions in SUV, mid-size and luxury vehicles.

Additionally this product is recommended when the following filling instructions are required:

- BMW L12108 (83 22 2 152 426)
- BMW 83 22 2 305 397
- BMW 83 22 2 289 720 (ATF3+)
- Chrysler 68157995AA
- FIAT 9.55550-AV5
- Honda Type 3.1
- Jaguar 02JDE 26444
- Jeep ATF LGF8
- Land Rover LR 023288/232289
- MB 236.82
- Mopar 68157995AA
- VW/Audi G 060 162 A1/A2/A6, G 055 162 (A2, A6)
- VW G 055 540 (A2)
- ZF Lifeguardfluid 8 (S671 090 312)
- ZF Lifeguardfluid 9 (AA01.500.001)
- ZF Lifeguard 6 (S671 090 255)

Advantages/Benefits

- Adapted friction coefficient behaviour for spontaneous and sporty shifting operations
- Prevention of friction vibrations in a reliable manner, thus providing maximum comfort
- Excellent friction coefficient stability over the entire service interval
- Reduced viscosity for better fuel efficiency
- Excellent shifting characteristics at low temperatures
- The best wear protection properties for reliable operation and the longest service life
- Highest oxidation and ageing stability due to a special base oil composition made of HC synthetic and fully synthetic PAO base oils
- Minimal tendency to foam
- Reliable protection against corrosion, wear, sludge accumulation and adhesion
- Neutral behaviour towards gasket materials
- Miscible and compatible with other ATF of the same specification. However, in order to exploit the full product benefits of GERMAN ADLER ATF 9-8, a complete oil change is strongly recommended.

Note: GERMAN ADLER ATF 9-8 is not recommended for use in DCT/DSG (Double Clutch Transmission) or CVT's (Continuous Variable Transmission)

Typical characteristics:

	Unit	Value	Method
Density at 15°C	kg/m ³	844	DIN 51 757
Viscosity at 40°C	mm ² /s	26,9	DIN 51 562
Viscosity at 100°C	mm ² /s	5,6	DIN 51 562
Viscosity index		157	DIN ISO 2909
Pour point	°C	-45	DIN ISO 3016
Flash point	°C	224	DIN ISO 2592
Colour		green	

The above data are true and correct to the best of our knowledge and belief and reflect the current state of knowledge and our development effort. All rights to changes reserved! The characteristic data indicated are subject to the repeatability and reproducibility of the given test methods.