



GERMAN ADLER GMBH

Kennedyallee 93
60596 Frankfurt am Main
Phone: +49 69 697 692 10
Fax: +49 69 697 962 15
info@german-adler.com
www.German-Adler.com

PRODUCT INFORMATION **GERMAN ADLER TX SYNT SAE 10W-30 CK-4**

Description

GERMAN ADLER TX SYNT SAE 10W-30 CK-4 is a high-performance engine oil based on the newest additive technology, matched with special base oils. It was developed for the latest generation of low-emission engines and provides excellent fuel economy. Due to the lower ash content as well as its outstanding oxidation and shear stability, it is used in modern truck engines.

Application

In compliance to EEC regulations the quality of GERMAN ADLER TX SYNT SAE 10W-30 CK-4 is equivalent according to the following standards / specifications:

- ACEA E7/E11
- API CK-4/CJ-4/SN
- API CI-4/CI-4 Plus
- CAT ECF-3
- Cummins CES 20086
- DAF PSQL 2.1E
- Detroit Diesel DFS93K222
- Detroit Diesel DDC93K222
- Deutz DQC-III-10LA/18LA
- Ford WSS-M2C171-F1
- Jaso DH-2
- Mack EOS-4.5
- MAN M 3575/M 3775/M 3275
- MB 228.31
- MTU Type 2.1
- Renault VI RLD-3
- Volvo VDS-4.5

Advantages/Benefits

- GERMAN ADLER TX SYNT SAE 10W-30 CK-4 is used as SHPD oil in engines with and without particulate filter and catalytic converter. It meets the special requirements of Low SAPS technology and is reliable in terms of cold start behavior and lubricity at high temperatures.
- GERMAN ADLER TX SYNT SAE 10W-30 CK-4 complies with the current API CK-4 and is excellently suited for use in EURO 2, EURO 3, EURO 4, EURO 5 und EURO 6 engines in combination with diesel fuel up to 500ppm sulfur content.
- miscible and compatible with conventional, also as synthetic branded engine oils. To make use of the full performance benefit of GERMAN ADLER TX SYNT SAE 10W-30 CK-4 a complete oil change is recommended

Typical characteristics:

	Unit	Value	Method
Density at 15°C	kg/m ³	859	DIN 51 757
Viscosity at 40°C	mm ² /s	75	DIN 51 562
Viscosity at 100°C	mm ² /s	11,8	DIN 51 562
Viscosity index	-	154	DIN ISO 2909
CCS at -25°C	mPa.s	5460	DIN 51 377
Pour point	°C	-39	DIN ISO 3016
Flash point	°C	236	DIN ISO 2592
Sulphated ash	mass.%	0,95	DIN 51 575
Sulphur	mass.%	0,36	ICP
Phosphorous	mass.%	0,11	ICP
TBN	mg KOH/g	10,2	DIN ISO 3771

The above data are true and correct to the best of our knowledge and belief and reflect the current state of knowledge and our development effort. All rights to changes reserved! The characteristic data indicated are subject to the repeatability and reproducibility of the given test methods.