



GERMAN ADLER GMBH

Kennedyallee 93
60596 Frankfurt am Main
Phone: +49 69 697 692 10
Fax: +49 69 697 962 15
info@german-adler.com
www.German-Adler.com

PRODUCT INFORMATION **GERMAN ADLER 2T-M**

Two-Stroke Motor Oil for Mixture and Separate Lubrication

Description

GERMAN ADLER 2-M is a 2-stroke motor oil based on mineral oil and applicable for 2-stroke which can be lubricated mixed (with fuel) or separately.

Application

GERMAN ADLER 2T-M is foreseen to be used in 2-stroke gasoline engines of mopeds, lawn mowers, concrete mixers and others if an oil of the API-classification TC is allowed. The mixing ratio of 2-stroke oil and fuel is recommended by the engine manufacturer, and it is desperate to regard that.

GERMAN ADLER 2-M is also suitable in mixture with leaded fuel.

Specification

- API TC
- SO-L-EGD
- JASO FD

Advantages/Benefits

- protects the engine against corrosion and wear
- prevents deposit built-up in the combustion chamber, on the exhaust slits and on the sparking plugs
- is self-mixing and forms a homogene mixture with the fuel

Typical characteristics:

	Unit	Value	Method
Density at 15°C	kg/m ³	871	DIN 51 757
Viscosity at 40°C	mm ² /s	108,0	DIN 51 562
Viscosity at 100°C	mm ² /s	11,5	DIN 51 562
Pour point	°C	-30	DIN ISO 3016
Flash point	°C	200	DIN ISO 2592
TBN	mg KOH/g	1	DIN ISO 3771
Sulphated ash	% mass.	0,07	DIN 51 575

The above data are true and correct to the best of our knowledge and belief and reflect the current state of knowledge and our development effort. All rights to changes reserved! The characteristic data indicated are subject to the repeatability and reproducibility of the given test methods.