



GERMAN ADLER GMBH

Kennedyallee 93

60596 Frankfurt am Main

Phone: +49 69 697 692 10

Fax: +49 69 697 962 15

info@German-Adler.com

www.German-Adler.com

PRODUCT INFORMATION **GERMAN ADLER 4T-S 10W-40**

High-Performance engine oil, made from HC-synthesis base oils. Specially developed for 4-stroke motor bikes equipped with joined oil circuit for engine, transmission wet clutches.

Description

GERMAN ADLER 4T-S 10W-40 is made from HC-synthesis and selected base oils in combination specially designed additives. This unique composition of selected base oils with a modern additive package provides its outstanding performance level.

Application

GERMAN ADLER 4T-S 10W-40 has been specially designed for use in 4-stroke motor bikes with joined oil circuit for engine, wet clutch and transmission. It offers outstanding thermal resistance and provides stable lubricating film even under very high stress. Thereby it fulfills the stringent friction requirements of JASO MA2 for perfect clutch performance.

In compliance to EEC regulations the quality of GERMAN ADLER 4T-S 10W-40 is equivalent according to the following standards / specifications:

- ACEA A3-04
- API SN Plus
- JASO MA2

Advantages/Benefits

- superior wear and corrosion protection of engine and transmission
- stable lubricating film even under very hot oil temperatures and/or very high stress
- real all-season use due to outstanding viscosity-temperature behaviour and high shear stability
- superior clutch performance – fulfills the tightened requirements of JASO MA2
- very good cold start behaviour and lubrication of the engine
- oxidation protection through selected HC synthesis oil components and special additive technology
- reliably prevents from resin formation, varnishing and ring sticking of cylinders and pistons
- miscible and compatible with conventional, also as synthetic branded engine oils. To make use of the full performance benefit of GERMAN ADLER 4T-S 10W-40 a complete oil change is recommended

Typical characteristics:

	Unit	Value	Method
Density at 15°C	kg/m ³	852	DIN 51 757
Viscosity at 40°C	mm ² /s	97	DIN 51 562
Viscosity at 100°C	mm ² /s	15,3	DIN 51 562
Viscosity index		167	DIN ISO 2909
Dynamic viscosity at -25°C	mPa.s	5290	DIN 51 377
Pour point	°C	-39	DIN ISO 3016
Flash point	°C	230	DIN ISO 2592
TBN	mg KOH/g	6,2	DIN ISO 3771

The above data are true and correct to the best of our knowledge and belief and reflect the current state of knowledge and our development effort. All rights to changes reserved! The characteristic data indicated are subject to the repeatability and reproducibility of the given test methods.